


Super Fast Recovery Bridge Rectifiers

Features

- UL recognition, file #E230084
- Glass passivated chip junction
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.



Mechanical Data

Package: PB

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102

Polarity: As marked on body

Maximum Ratings ($T_a=25$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	EPB35
-----------	--------	------	-------



EPB3506

Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	
Maximum reverse recovery time	T_{RR}	ns	$I_F=0.5A, I_R=1.0A,$ $I_{RR}=0.25A$	50
Maximum instantaneous forward voltage drop per diode	V_F	V	$I_{FM}=17.5A$	2.0
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	$T_j=25$	5
			$T_j=125$	100
Typical junction capacitance	C_j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	175

Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER		SYMBOL		EPB3506
Typical Thermal Resistance	Between junction and ambient, Without heatsink	R_{JA}	/W	17.0
	Between junction and case, With heatsink	R_{JC}		0.8

Mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

Marking Information (Example)

ORDER P/N	CODE



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controller