



YBSML8006

Thermal Characteristics $T_a=25$ Unless otherwise specified


PARAMETER		SYMBOL	UNIT	YBSML8006
Typical Thermal Resistance	Between Junction and Ambient	R_{J-A}	/W	55
	Between Junction and Lead	R_{J-L}		10
	Between Junction and Case	R_{J-C}		5

Note: Device mounted on P.C.B with 35mm*25mm*1.7mm.

Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YBSML8006	F1	Approximate 0.38	1800	/	25200	13" Reel

Characteristics (Typical)





Outline Dimensions

YBS3		
Dim	Min	Max
A	10.00	10.40
B	9.70	10.10
C	6.80	7.20
D	1.3	1.5

Suggested pad layout



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.