


# YJ Planar Schottky Barrier Diode Die Specification

200V 3A, 60mil, Schottky barrier diode die based on silicon planar process  
Part No.: PSB060H200SS-280A



## Main Products Characteristics

### Maximum Ratings

Parameter	Symbol	Rating
Repetitive peak reverse voltage	$V_{RRM}$	200 V
Average forward current	$I_{F(AV)}$	3A
( $t_p = 8.3$ ms, halfwave, 1 cycle)	$I_{FSM}$	80 A
Storage temperature range	$T_{stg}$	-50 to +175 °C
Maximum operating junction temperature	$T_j$	175 °C

### Static Electrical Characteristics ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	
		Spec	Typical
Reverse breakdown voltage $I_R = 1\text{mA}$	$V_{BR}$	210 V	230V
Maximum forward voltage drop $I_F = 3\text{A}$ 2%	$V_F$	0.85V	0.80V
Maximum reverse current $V_R = V_{RRM}$ 2%	$I_R$	5uA	0.2uA

## Device Schematics and Outline Drawing

Die Thickness *	11 Mils
Die Size **	60 Mils
Top Metal Pad	56 Mils
Active Area	52 Mils
Top Metal	Ag
Back Metal	Ag

Note: 1 \* : Also can offer device with 8 mils thickness  
2 \*\*: Cutting street width is around 1.5 mils

## Important Notice

<p>Specification apply to die only. Actual performance may degrade when assembled.</p> <p>does not guarantee device performance after assembly.</p> <p>All operating parameters must be validated for each customer application by customer's technical experts.</p> <p>Data sheet information is subjected to change without notice.</p>	<p>Recommended Storage Environment:</p> <p>Store in original container, in dessicated nitrogen, with no contamination.</p> <p>Shelf life for parts stored in above condition is 2 years.</p> <p>If the storage is done in normal atmosphere shelf life is reduced to 6 months.</p>
---	--

0514-80982389  
0514-80980189

Rev.O 2021/07/28