



# TSB75T060S(A)S-255A

5A/60V, low VF Schottky barrier diode with trench MOS structure

## Mechanical Data

Chip Drawing	Item	Information	
	Die Size (A)	1905 $\mu\text{m}$	75 mil
	Top Metal Pad Size (B)	1812 $\mu\text{m}$	71mil
	Chip Size (C)	1825 $\mu\text{m}$	72mil
	Wafer Thickness (D)	255 $\mu\text{m}$	9.5 mil
	Scribe Line Width (E)	80 $\mu\text{m}$	3.15 mil
	Wafer Size	6 inch	
	Top Side Metallization	TSB75T060SS-255A	Al/Ag
	Back Side Metallization	Ti Ni Ag	
	Recommended Storage Environment	Stored in original container, in dry nitrogen, (6 months at an ambient temperature of 23 $\pm$ 3 )	

## Electrical Characteristics (T<sub>J</sub>=25

)<sup>(1)</sup>

Parameter	Description	Min.	Typ.	Max.	Unit	Test Condition
V <sub>BR</sub>	Reverse Breakdown Voltage	62	70	-	V	I <sub>R</sub> =100 $\mu\text{A}$
V <sub>F</sub>	Instantaneous Forward Voltage	-	0.485	0.520	V	I <sub>F</sub> =5A <sup>(2)</sup>
I <sub>R</sub>	Reverse Leakage Current	-	5	40		V <sub>R</sub> =65V
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Temperature	-40	to 150	Max		

### Note:

(1) The preliminary wafer datasheet only for reference;

(2) This characteristics assumes the dies are assembled in DO-27 packages(Al Wire 15milX2). Actual performance may degrade when assembled. YJ does not guarantee device performance after assembly;

(3)