


1-Line, Uni-directional, Transient Voltage Suppressor



Features

- Stand-off voltage: 24V Max
- Transient protection for each line according to
 - IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
 - IEC61000-4-5(surge): 140A (8/20 μs)
- Low leakage current
- Low clamping voltage
- Low clamping voltage:
- RoHS Compliant

Applications


- Power Management
- Industrial Application
- Power Supply Protection

Mechanical Data

- Package: DFN2020-3L
- Case Material: "Green" Molding Compound
- Marking Information: See Below



Definitions of electrical characteristics





ESD24VP4A2

Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	7000	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{pp}	140	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	kV
ESD according to IEC61000-4-2 contact discharge		± 30	
Junction temperature	T_J	-55~125	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$

Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				24
Reverse leakage current	I_R	μA	$V_{RWM} = 24V$			1
Reverse breakdown voltage	V_{BR}	V	$I_{BR} = 1mA$	24.8		30
Clamping voltage ¹⁾	V_{CL}	V	$I_{PP} = 50A, t_p = 8/20\mu s$			32
		V	$I_{PP} = 140A, t_p = 8/20\mu s$			50
Junction capacitance	C_J	pF	$V_R = 0V, f = 1MHz$		410	

Notes:


(1). Non-repetitive current pulse, according to IEC61000-4-5.

Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD24VP4A2	F1	Approximate 010	3000	30000	120000	7" reel



Characteristics (Typical)





ESD24VP4A2

Outline Dimensions

Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	0.55	0.60	0.80
A1	0.00	0.02	0.05
A3	0.10 REF.		
b	0.25	0.30	0.35
D	1.90	2.00	2.10
E	1.90	2.00	2.10
D2	0.95	1.05	1.15
E2	1.40	1.50	1.60
e	1.20	1.30	1.40

Recommended PCB Layout

Unit:mm



ESD24VP4A2

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.