






# YJD45G10A

## Electrical Characteristics ( $T_j=25$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
<b>Static Parameter</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250$	100			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100, V_{GS}=0V$			1	
Gate-Body Leakage Current	$I_G$	657.7 151.				










Figure13.Normalized Maximum Transient thermal impedance



# YJD45G10A

## TO-252-B Package information



SYMBOL	INCHES				
	MIN.	NOM.			
A1	0.000				
A2	0.087	0.091			
A3	0.035	0.039			
b	0.026	0.030			
c	0.018	0.020			
D	0.256	0.260			
D1					
D2	0.181	0.189			
E	0.390	0.398			
E1	0.236	0.240			

**NOTE:**

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
- 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
- 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

