

\*\*\*\*\*



Peak gate power dissipation	$P_{GM}$		20		W	
Average gate power dissipation	$P_{G(AV)}$		4		W	
Gate-trigger current	$I_{GT}$		120		mA	$V_D = 12\text{ V}; R_L = 3\text{ ohms}; T_j = +25\text{ }^\circ\text{C}$
Gate- trigger voltage	$V_{GT}$	0.70	2.5		V	$V_D = 12\text{ V}; R_L = 3\text{ ohms}; T_j = +25\text{ }^\circ\text{C}$
Peak negative voltage	$V_{GRM}$		5		V	

Delay time	$t_d$		3.0	2.5	s	$I_{TM}=100\text{A}; V_D=67\%V_{DRM}$ $V_G=30\text{V}; R_G=10\text{ohms};$ $t_r=0.1\text{ s}; t_p=20\text{ s}$
Turn-off time (with $V_R = -5\text{ V}$ )	$t_q$			150	s	$I_{TM} = 500\text{A}; di/dt = -10\text{A/ s};$ $V_R = 100\text{V}; dv/dt=30\text{V/ s};$ $V_D=67\%V_{DRM}; T_j=125$
Reverse recovery charge	$Q_{rr}$				C	$I_{TM}=500\text{A } di/dt=-10\text{A/ s};$ $V_R=100\text{V}; T_j=125$

Operating temperature	$T_j$	-40	+125		$^\circ\text{C}$	
Storage temperature	$T_{stg}$	-40	+140		$^\circ\text{C}$	
Thermal resistance - junction to case	$R_{(j-c)}$		0.08		$^\circ\text{C/W}$	Double sided cooled
Thermal resistance - case to heatsink	$R_{(c-s)}$		0.02		$^\circ\text{C/W}$	Double sided cooled
Mounting force	F	3.5	4.5	4	kN	
Weight	m			0.05	kg	

\* Mounting surfaces smooth, flat and greased



