

\*\*\*\*\*



Peak gate power dissipation	$P_{GM}$		20		W	
Average gate power dissipation	$P_{G(AV)}$		4		W	
Gate-trigger current	$I_{GT}$		200		mA	$V_D = 12\text{ V}; R_L = 3\text{ ohms}; T_j = +25\text{ }^\circ\text{C}$
Gate- trigger voltage	$V_{GT}$	0.7	2.6		V	$V_D = 12\text{ V}; R_L = 3\text{ ohms}; T_j = +25\text{ }^\circ\text{C}$
Peak negative voltage	$V_{GRM}$		10		V	

Delay time	$t_d$		3.0	s	$I_{TM}=100\text{A}; V_D=67\%V_{DRM}$ Gate pulse: $V_G=30\text{V}; R_G=10\text{ohms};$ $t_r=0.1\text{ s}; t_p=20\text{ s}$
Turn-off time (with $V_R = -5\text{ V}$ )	$t_q$		800	s	$I_{TM} = 2000\text{A}; di/dt = -10\text{A/ s};$ $V_R = 100\text{V}; dv/dt = 30\text{V/ s};$ $V_D = 67\%V_{DRM}; T_j = 110$
Reverse recovery charge	$Q_{rr}$		3500	C	$I_{TM}=2000\text{A } di/dt=-10\text{A/ s};$ $V_R=100\text{V}; T_j=110$

1n 06



