

WITC

HY IS

00V

\*\*\*

\*\*\*

\*\*\*

\*\*\*

## ELECTRICAL CHARACTERISTICS AND RATINGS KK1500-FAST SWITCHING THYRISTOR

### Gating

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Peak gate power dissipation	$P_{GM}$		20		W	
Average gate power dissipation	$P_{G(AV)}$		4		W	
Gate-trigger current	$I_{GT}$		150		mA	$V_D=12V; R_L=3ohms; T_j=+25^{\circ}C$
Gate- trigger voltage	$V_{GT}$	0.70	2.5		V	$V_D=12V; R_L=3ohms; T_j=+25^{\circ}C$
Peak negative voltage	$V_{GRM}$		5		V	

### Dynamic

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Delay time	$t_d$		3.0	2.5	s	$I_{TM}=1000A; V_D=67\%V_{DRM}$ Gate pulse: $V_G=30V; R_G=10ohms;$ $t_r=0.1 s; t_p=20 s$
Turn-off time (with $V_R = -5 V$ )	$t_q$		70		s	$I_{TM} = 1500 A; di/dt = - 25A/ s;$ $V_R = 50 V; dv/dt=30V/ s;$ $V_D= 67\%V_{DRM}; T_j=125^{\circ}C$
Reverse recovery charge	$Q_{rr}$				C	$I_{TM}=1500 A; di/dt=-10A/ s;$ $V_R=50 V; T_j=125^{\circ}C$

## THERMAL AND MECHANICAL CHARACTERISTICS AND RATINGS

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Operating temperature	$T_j$	-40	+125		$^{\circ}C$	
Storage temperature	$T_{stg}$	-40	+140		$^{\circ}C$	
Thermal resistance - junction to case	$R_{(j-c)}$		0.016		$^{\circ}C/W$	Double sided cooled
Thermal resistance - case to heatsink	$R_{(c-s)}$		0.005		$^{\circ}C/W$	Double sided cooled
Mounting force	F	25	31	28	kN	
Weight	m			0.65	kg	

\* Mounting surfaces smooth, flat and greased


9