



Positive temperature coefficient
 Temperature-independent switching
 Maximum working temperature at 175 °C
 Unipolar devices and zero reverse recovery current
 Zero forward recovery current
 Essentially no switching losses
 Reduction of heat sink requirements
 High-frequency operation
 Reduction of EMI

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

: TO-263
 : Tin plated leads
 : As marked


(T_c=25 Unless otherwise specified)

Device marking code			D112020BXGG2
Reverse voltage (repetitive peak) @ T _j =25°C	V _{RRM}	V	1200
Reverse voltage (Surge Peak) @ T _j =25°C	V _{RSM}	V	1200
Reverse voltage (DC) @ T _j =25°C	V _{DC}	V	1200
Continuous forward current @ T _c =25°C T _c =135°C T _c =141°C	I _F	A	56 25 20
Non-repetitive peak forward surge current @ T _c =25°C, tp=10ms, Half Sine Wave	I _{FSM}	A	160
Power Dissipation @ T _c =25°C T _c =110°C	P _{TOT}	W	214 92
i ² t Value @ T _c =25°C ,tp=10ms	i ² dt	A ² S	128

iSM 0te



Forward voltage drop	V_F	V	$I_F=20A, T_j=25^{\circ}C$	1.34	1.55
			$I_F=20A, T_j=175^{\circ}C$	1.86	2.70
Reverse leakage current	I_R	μA	$V_R=1200V, T_j=25^{\circ}C$	0.5	25



TO-263

Dim	Min	Max	
A	9.5	10.5	A
B	0.5	0.5	B
C	8.4	9.0	C
D	0.28	0.64	D
E	0.68	0.94	E
F	4.55	5.6	F
G	4.04	5.10	G
H	1.14	1.4	H
I	0	0.2	I
J	4.9	6.05	J
K	1.79	2.79	K
L	7.3	7.9	L
M	6.2	6.8	M
N	7.6	8.2	N



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.