



Switching Diodes

Features

Epoxy meets UL-94 V-0 flammability rating

Surface mount package ideally Suited for Automatic Insertion

Moisture Sensitivity Level 1

Mechanical Data

Package: SOT-363

Terminals: Tin plated leads, solderable per

J-STD-002 and JESD22-B102

Mark :



MMBD4448 HSDW/ HTW/ HAQW/ HADW/ HCDW

Maximum Ratings (Ta=25 Unless otherwise specified)

PARAMETER		UNIT		
Non-Repetitive peak reverse voltage	V_{RM}	V		100
Repetitive peak reverse voltage	V_{RRM}	V		80
Reverse voltage	V_R	V		80
Peak forward surge current	I_{FSM}	A	Pulse width=1 us Pulse width=1 s	2 0.5
Average forward current	I_{FAV}	mA		150
Power dissipation	P_D	mW		200
Thermal Resistance Junction to Ambient Air	R_{JA}	/W		625
Maximum junction temperature	T_j			-55 ~+150
Storage temperature range	T_{stg}			-55 ~+150



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales es s