



Surface mount package ideally suited for automatic insertion

Application

Signal amplification
Switching circuit

Mechanical

Maximum Ratings ($T_a=25$ Unless otherwise specified)

DTR1-NPN

Item	Symbol	Unit	Conditions	Value
Device marking code				D6
Collector-base voltage	V_{CBO}	V	$I_C=50\mu A$	50
Collector-emitter voltage	V_{CEO}	V	$I_C=1mA$	50
Emitter-base voltage	V_{EBO}	V	$I_E=50\mu A$	5
Collector current	I_C	mA		100
Power dissipation	P_D	mW		150
Junction temperature	T_J			-55 to +150
Storage temperature	T_{STG}			-55 to +150

**DTR2-PNP**

Item	Symbol	Unit	Conditions	Value
Collector-base voltage	V_{CBO}	V	$I_C=-50\mu A$	-50
Collector-emitter voltage	V_{CEO}	V	$I_C=-1mA$	-50
Emitter-base voltage	V_{EBO}	V	$I_E=-50\mu A$	-5
Collector current	I_C	mA		-100
Junction temperature	T_J			-55 to +150
Storage temperature	T_{STG}			-55 to +150

Electrical Characteristics ($T_a=25$ Unless otherwise specified)**DTR1-NPN**

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	$I_C=50\mu A$	50		
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	$I_C=1mA$	50		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	$I_E=50\mu A$	5		
Collector-base cut-off current	I_{CBO}	μA	$V_{CB}=50V$			0.5
Emitter-base cut-off current	I_{EBO}	μA	$V_{EB}=4V$			0.5
DC current gain	h_{FE}		$V_{CE}=5V, I_C=1mA$	100		600
Input resistance	R_1	k		3.29	4.7	6.11
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C=10mA, I_B=0.5mA$			0.3
Transition frequency	f_T	MHz	$V_{CE}=10V, I_E=-5mA, f=100MHz$		250	

Characteristics

DTR1-NPN

Fig 1 Static Characteristics




Fig 2 DC Current Gain Characteristics




Fig 3 Collector-Emitter Saturation Voltage





Fig 4 P_D - T_a Curve



DTR2-PNP

Fig 4 Static Characteristics




Fig 5 DC Current Gain Characteristics





Fig 6 Collector-Emitter Saturation Voltage







Ordering Information

Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
UMD6N	F2	Approximate 0.009	3000	30000	120000	7" reel
UMD6N	F3	Approximate 0.009	10000	/	210000	7" reel

Outline Dimensions



Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.