




Maximum RMS Voltage	V _{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V _{DC}	V	50	100	200	400	600	800	1000

Average Forward Current
@60Hz sine wave, Resistance load, Ta=65

	FSM	A	200	
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			400	
Current squared time @1ms≤t≤8.3ms Tj=25 Rating of per diode	I²t	A²s	166	
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj	pF	70	56
Storage Temperature	Tstg		-55 ~ +150	
Junction Temperature	Tj		-55 ~ +150	

$T_a=25$ Unless otherwise specified

[illegible]

v7KHUPDO &KDUDFWHULVWLFV RWKHU⁷LVH VSHFLILHG





3\$5\$0(7(5	6<0%2	81,7	)5 *	)5 *	)5 *	)5 *	)5 *	)5 *	)5 *
7\SLFDO 7KHUPDO 5HVLVWDQF:H									

v2UGHULQJ ,QIRUPDVLHQ

35()(5(' 3 1	3\$&.\$*(&2'()	81,7 :(*+7	0,1,080 3\$&.\$*(SFV	,11(5 %2; 48\$17,7< SF	287(5 &\$572 48\$17,7< SF	'(/,9(5< 02'()
)5 *a)5 *	'	\$SSUR[LPDWH				
)5\$ *a)5 *	&	\$SSUR[LPDWH				

7DSH
%XO

v8KDUDFWHULVWLFV



,QVWDQWDQHRXV 9ROWDJH

3HUFHQW RI 5DWHG 3HDN 5HYHUVH 9ROWD





The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility.