

**1N5817, 1N5818, 1N5819**

For use in low voltage high frequency inverters,

Tin plated leads, solderable per J-STD-002 and JESD22-B102

Color band denotes the cathode end

Unless otherwise specified (Ta=25 °C)

Parameter	Symbol	Unit	1N5817	1N5818	1N5819
Device marking code			1N5817	1N5818	1N5819
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	V	20	30	40
Average Rectified Output Current @60Hz sine wave, Resistance load, Ta (FIG.1)	I <sub>O</sub>	A	1.0		
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Ta=25	I <sub>FSM</sub>	A	30		
Storage Temperature	T <sub>stg</sub>		-55 ~+150		
Junction Temperature	T <sub>j</sub>		-55 ~+125		

High Frequency Rectifier

Parameter	Symbol	Unit	1N5817	1N5818	1N5819
Typical junction capacitance	C <sub>j</sub>	pF	60	50	

Note1: Pulse test: 300uS pulse width, 1% duty cycle

Solder dip 275 °C max. 7 s, per JESD 22-B106

High frequency operation

v7KHUPDO & KDUDÄF7WHU&QVHLVVRWKHUÅLVH VSHFLILHG

3\$5\$0(7(5	6<0%2/	81,7	1	1	1
7KHUPDO 5HVLVW	DQ5Hs	:			

v2UGHULQJ ,QIRUPDWLRQ ([DP SOH

35()(5(' 3 1	3\$&.\$*( &2'( 81,7 :(*+7 J	0,1,080	,11(5 %2;
		3\$&.\$*( SFV	





8]gW`U] a Yf`

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for t