



High frequency operation
 High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
 Guard ring for enhanced ruggedness and long term reliability
 Solder dip 275 °C max. 7 s, per JESD 22-B106

: Tin plated leads, solderable per J-STD-002 and JESD22-B102
 : As marked

Device marking code			MBR10100CTS	MBR10150CTS	MBR10200CTS
Repetitive Peak Reverse Voltage	V_{RRM}	V	100	150	200
Average Rectified Output Current @60Hz sine wave, R-load, $T_a=25$	I_o	A	10		
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, $T_a=25$	I_{FSM}	A	100		
Current Squared Time @1ms $t < 8.3ms$ $T_j=25$	I^2t	A^2s	42		
Storage Temperature	T_{stg}		-55 ~ +175		
Junction Temperature	T_j		-55 ~ +175		

$T_a=25$ Unless otherwise specified

Maximum instantaneous forward voltage drop per diode	V_{FM}	V	$I_{FM}=5.0A$	0.85	0.9	0.95
Maximum DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	mA	$V_{RM}=V_{RRM}$ $T_a=25$	0.1		
	I_{RRM2}		$V_{RM}=V_{RRM}$ $T_a=125$	20		

Note1:Pulse test:300uS pulse width,1% duty cycle

Note2:Pulse test:pulse width 40mS




T_a=25 Unless otherwise specified

Thermal Resistance	Between junction and case	R _{J-C}	/W	2.0		

(Example)

MBR10100CTS THRU MBR10200CTS	Approximate 1.9	50	1000	5000	Tube	

(Typical)



Dim	Min	Max
A	9.95	10.35
B	2.55	2.95
C	3.8	4.0
D	14.95	15.25
E	3.75	4.25
F	0.26	0.5
G	0.68	0.94
H	13.4	13.9
I	2.35	2.65
J	4.38	4.78
K	1.14	1.4
L	2.37	2.79

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.