


Schottky Diodes



Features

- High frequency operation
- Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

Package: ITO-220AB

Molding compound meets UL 94 V-0 flammability

Device marking code			MBR1045FCT
Repetitive Peak Reverse Voltage	V_{RRM}	V	45
Average Rectified Output Current @60Hz sine wave, R-load, T_c (FIG.1)	I_o	A	10
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, $T_j=25$	I_{FSM}	A	100
Surge(Non-repetitive)Forward Current @1ms square wave, 1 time, $T_j=25$			200
Current Squared Time @1ms t 8.3ms $T_j=25$	I^2t	A^2s	41
Typical junction capacitance M Applied Reverse Voltage of 4.0 V.D.C.	C_j	pF	273
Storage Temperature	T_{stg}		-55 ~ +150
Junction Temperature	T_j		-55 ~ +150
Mounting torque @recommend torque 5kg cm	Tor	kg cm	8



MBR1045FCT


Electrical Characteristics Specified Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
			$I_{FM}=5.0A$	0.5	0.51	0.55



FIG.4: Typical Rever

T O



Outline Dimensions

ITO-220AB		
Dim	Min	Max
A	9.8	10.2
B	2.25	2.75
C	2.95	3.45
D	14.75	15.25
E	3.05	3.95
F	0.45	0.75
G	0.45	0.75
H	13.4	14.2
I	2.35	2.75
J	4.3	4.8
K	2.58	2.82
L	2.58	2.82
M	1.47	1.77



MBR1045FCT

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.