



# MBR3060PT

## Schottky Diodes

### Features

High frequency operation  
High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance  
Guard ring for enhanced rugged

**Terminals:** Tin plated leads, solderable per 002 and JESD22-B102

**Polarity:** As marked

### Maximum Ratings ( $T_a=25$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MBR3060PT
Device marking code			MBR3060PT
Repetitive Peak Reverse Voltage	$V_{RRM}$	V	60
Average Rectified Output	I		
	$t$	$A^2s$	260
Storage Temperature	$T_{stg}$		&



# MBR3060PT

---

TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1		



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.