
**Mechanical Data**● **Package:** TO-277

Molding compound meets UL 94 V-0 flammability rating,
RoHS-compliant, Halogen free

● **Terminals:** Tin plated leads, solderable per
J-STD-002 and JESD22-B102**■ Maximum Ratings** ($T_a=25$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS15U100T
Device marking code			SS15U100T
Repetitive Peak Reverse Voltage	V_{RRM}	V	100
Average Rectified Output Current @60Hz -sine wave, R- load, $T_c=97.5$	I_O	A	15
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, $T_a=25$	I_{FSM}	A	200
Current Squared Time @1ms ≤ t ≤ 8.3ms $T_j=25$	I^2t	A ² s	166
Storage Temperature	T_{stg}		-55 ~ +150
Junction Temperature	T_j		-55 ~ +150

■ Electrical Characteristics ($T_a=25$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Peak Forward Voltage	V_{FM}	V	$I_{FM}=15.0A, T_j=25$	-	0.69	0.82
			$I_{FM}=15.0A, T_j=125$	-	0.6	0.72
Reverse Breakdown Voltage	V_{BR}	V	$I_R=0.5mA$	100	-	-
Leakage Current	I_R	mA	$V_R=100V, T_j=25$	-	-	0.2
			$V_R, T_j=25 -$			



SS15U100T


■ Thermal Characteristics ($T_a=25$ Unless otherwise specified)


PARAMETER		SYMBOL	UNIT	SS15U100T
Thermal Resistance	Junction to Case	$R_{\theta J-C}$	/W	8

■ Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SS15U100T	F1	Approximate 0.0821	5000	10000	80000	13" reel

■ Characteristics (Typical)





TO-277		
Dim	Min(mm)	Max(mm)
A	3.9	4.1
B	1.7	1.9
C	6.4	6.6
D	5.3	5.5
E	0.8	1.0
F	1.8	1.9
G	0.35	0.45
H	1.10	1.20
I	4.1	4.5
J	1.5	1.9

TO-277	
Dim	Min(mm)
A	3.36
B	4.86
C	0.85
P	1.84
Q1	1.4
Q2	1.4



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.