



# SSL24A THRU SSL210A

## Surface Mount Schottky Rectifier

### Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

### Mechanical Data

#### Package

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

**Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

**Polarity:** Cathode line denotes the cathode end

### Maximum Ratings ( $T_a=25$ Unless otherwise specified)

			SSL24A	SSL26A	SSL210A
Device marking code			SSL24A	SSL26A	SSL210A
Repetitive peak reverse voltage	$V_{RRM}$	V	40	60	100
Average rectified output current @60Hz sine wave, resistance load, TL (FIG.1)	$I_O$	A	2.0		
Surge(non-repetitive)forward current @ 60Hz half-sine wave,1 cycle, $T_a=25$	$I_{FSM}$	A	50		
Storage temperature	$T_{stg}$		-55 ~+150		
Junction temperature	$T_j$		-55 ~+150		

### Electrical Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	SSL24A	SSL26A	SSL210A
Maximum instantaneous forward voltage drop per diode	$V_F$	V	$I_{FM}=2.0A$	0.47	0.55	0.75
Maximum DC reverse current at rated DC blocking voltage per diode @ $V_{RM}=V_{RRM}$	$I_{RRM}$	mA	$T_a=25$	0.50		
			$T_a=100$	10		

# SSL24A THRU SSL210A



## Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	SSL24A	SSL26A	SSL210A
Thermal resistance	$R_{J-A}$	/W	60 <sup>1)</sup>		
	$R_{J-L}$		20 <sup>1)</sup>		

Note  
 (1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

## Characteristics (Typical)

FIG1  $I_o$  TL Curve





## SSL24A THRU SSL210A

---

### Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
-----------------	-----------------	----------------	-------------------------	----------------------------	-------------------------------	------------------



## SSL24A THRU SSL210A

---

### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.